


NCSform 200



结构参数 Construction Specification

● 内导体 Inner conductor	裸铜线 Solid Copper	1.12 mm
● 绝缘体 Dielectric	发泡聚乙烯 Foam Polyethylene	2.95 mm
● 外导体 Outer conductor	自粘铝箔 Bonded Aluminum Foil	3.07 mm
	镀锡铜线编织 Tinned Copper Braid	3.66 mm
● 外护套 Jacket	聚乙烯 Black PE or PVC	4.95 mm

电性能参数 Electrical Characteristics

● 电容 Capacitance (pF/m)	80.4
● 阻抗 Impedance (ohm)	50
● 传输速率 Velocity of Propagation (%)	83
● 弯曲半径 Bending radius (mm)	25
● 峰值功率 Max.oper.Power (KW)	2.5
● 最大工作电压 Max.oper. voltage (VMS)	3000
● 最大工作频率 Max.oper. frequency (MHz)	39
● 工作温度范围 Operating Temp.(°C)	-25 to +70

衰减(>dB/m)和平均功率(Watts CW) (20°C, 海平面测试条件) Attenuation(>dB/m) & Average Power(Watts CW) @20°C and Sea Level

频率(MHz)	衰减/ Attenuation (dB/m)	功率/Power (Watts CW)
● 50	0.075	0.79
● 150	0.131	0.45
● 220	0.159	0.37
● 450	0.228	0.26
● 900	0.326	0.18
● 1500	0.424	0.14
● 1800	0.466	0.13
● 2000	0.493	0.12
● 2500	0.554	0.10
● 3000	0.865	0.07